

# Safety data sheet

Page: 1/8

BASF Safety data sheet according to Regulation (EC) No. 1907/2006

Date / Revised: 29.11.2009

Version: 1.0

Product: **Masterseal SP120 PF Lt Grey, Base**

(454267/SDS\_GEN\_EU/EN)

Date of print 21.10.2010

## 1. Identification of the substance/mixture and of the company/undertaking

### Masterseal SP120 PF Lt Grey, Base

Company:

BASF South East Asia Pte Ltd.

7 Temasek Boulevard,

#35-01 Suntec Tower One, 038987, SINGAPORE

Contact address:

BASF SE

67056 Ludwigshafen

GERMANY

Telephone: +49 621 60-0

E-mail address: global.info@basf.com

Emergency information:

International emergency number:

Telephone: +49 180 2273-112

---

## 2. Hazards Identification

**Possible Hazards** (according to Directive 67/548/EWG or 1999/45/EC)

Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## 3. Composition/Information on Ingredients

Chemical nature

Preparation based on: epoxy resin

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006

Date / Revised: 29.11.2009

Version: 1.0

Product: **Masterseal SP120 PF Lt Grey, Base**

(454267/SDS\_GEN\_EU/EN)

Date of print 21.10.2010

---

#### Hazardous ingredients

according to Directive 1999/45/EC

Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)

Content (W/W): > 10 % - < 50 %

CAS Number: 25068-38-6

EC-Number: 500-033-5

INDEX-Number: 603-074-00-8

Hazard symbol(s): Xi, N

R-phrases: 36/38, 43, 51/53

The wording of the hazard symbols and R-phrases is specified in chapter 16 if dangerous ingredients are mentioned.

---

## 4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

On skin contact:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

---

## 5. Fire-Fighting Measures

Suitable extinguishing media:

foam, water spray, dry extinguishing media, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental Release Measures

### Personal precautions:

Use personal protective clothing. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods for cleaning up or taking up:

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

---

## 7. Handling and Storage

### Handling

Avoid contact with the skin, eyes and clothing.

### Protection against fire and explosion:

The substance/product is non-combustible. The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

### Storage

Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

---

## 8. Exposure Controls/Personal Protection

### Personal protective equipment

#### Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and other  
Manufacturer's directions for use should be observed because of great diversity of types.

#### Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

#### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

**General safety and hygiene measures:**

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

---

**9. Physical and Chemical Properties**

|                         |                                   |                   |
|-------------------------|-----------------------------------|-------------------|
| Form:                   | paste                             |                   |
| Colour:                 | light grey                        |                   |
| Odour:                  | resinous                          |                   |
| Boiling point:          | not applicable                    |                   |
| Flash point:            | not applicable                    |                   |
| Flammability:           | does not ignite                   |                   |
| Ignition temperature:   | not applicable                    |                   |
| Self ignition:          |                                   | not self-igniting |
| Explosion hazard:       | not explosive                     |                   |
| Density:                | 1.51 g/cm <sup>3</sup><br>(25 °C) |                   |
| Solubility in water:    | insoluble                         |                   |
| Miscibility with water: | immiscible                        |                   |
| Viscosity, dynamic:     | 300 - 400 mPa.s<br>(25 °C)        |                   |

---

**10. Stability and Reactivity****Conditions to avoid:**

See MSDS section 7 - Handling and storage.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

**Substances to avoid:**

strong acids, strong bases, strong oxidizing agents

**Hazardous reactions:**

The product is stable if stored and handled as prescribed/indicated.

---

## 11. Toxicological Information

### Acute toxicity

Assessment of acute toxicity:  
Virtually nontoxic after a single ingestion.

Experimental/calculated data:  
LD50 rat (oral): > 10,000 mg/kg

### Irritation

Assessment of irritating effects:  
Eye contact causes irritation. Skin contact causes irritation.

### Respiratory/Skin sensitization

Assessment of sensitization:  
Sensitization after skin contact possible.

Experimental/calculated data:  
The European Union (EU) has classified this substance as skin-sensitizing (R43).

---

## 12. Ecological Information

### Ecotoxicity

Assessment of aquatic toxicity:  
Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. The product has not been tested. The statement has been derived from the properties of the individual components.

Toxicity to fish:  
LC50 (96 h) 1.41 mg/l, *Oryzias latipes* (JIS K 0102-71, semistatic)  
The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates:  
EC50 1 - 10 mg/l, daphnia  
Literature data. The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic plants:  
EC50 (96 h) 9.1 mg/l, *Selenastrum capricornutum* (Algal growth inhibition test, static)  
The product has not been tested. The statement has been derived from the properties of the individual components.

Microorganisms/Effect on activated sludge:  
EC50 > 100 mg/l, activated sludge (aquatic)

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006

Date / Revised: 29.11.2009

Version: 1.0

Product: **Masterseal SP120 PF Lt Grey, Base**

(454267/SDS\_GEN\_EU/EN)

Date of print 21.10.2010

---

Literature data.

**Additional information**

Other ecotoxicological advice:

Acutely toxic for aquatic organisms. Do not discharge product into the environment without control.

---

**13. Disposal Considerations**

Observe national and local legal requirements.

Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

**14. Transport Information****Land transport**

ADR

|                       |   |
|-----------------------|---|
| Hazard class:         | 9   |
| Packing group:        | III   |
| ID number:            | UN 3082   |
| Hazard label:         | 9, EHSM   |
| Proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700) |

RID

|                       |   |
|-----------------------|---|
| Hazard class:         | 9   |
| Packing group:        | III   |
| ID number:            | UN 3082   |
| Hazard label:         | 9, EHSM   |
| Proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700) |

**Inland waterway transport**

ADNR

|                       |   |
|-----------------------|---|
| Hazard class:         | 9   |
| Packing group:        | III   |
| ID number:            | UN 3082   |
| Hazard label:         | 9, EHSM   |
| Proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700) |

BASF Safety data sheet according to Regulation (EC) No. 1907/2006

Date / Revised: 29.11.2009

Version: 1.0

Product: **Masterseal SP120 PF Lt Grey, Base**

(454267/SDS\_GEN\_EU/EN)

Date of print 21.10.2010

**Sea transport****IMDG**

|                       |   |
|-----------------------|---|
| Hazard class:         | 9   |
| Packing group:        | III   |
| ID number:            | UN 3082   |
| Hazard label:         | 9, EHSM   |
| Marine pollutant:     | YES   |
| Proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700) |

**Air transport****IATA/ICAO**

|                       |   |
|-----------------------|---|
| Hazard class:         | 9   |
| Packing group:        | III   |
| ID number:            | UN 3082   |
| Hazard label:         | 9, EHSM   |
| Proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700) |

**15. Regulatory Information****Regulations of the European union (Labelling) / National legislation/Regulations**as in Annex I of Directive 67/548/EEC:**Hazard symbol(s)**

|    |                                |
|----|--------------------------------|
| Xi | Irritant.                      |
| N  | Dangerous for the environment. |

**R-phrase(s)**

|        |   |
|--------|---|
| R36/38 | Irritating to eyes and skin.  |
| R43    | May cause sensitization by skin contact.  |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

**S-phrase(s)**

|        |   |
|--------|---|
| S2     | Keep out of the reach of children.  |
| S28    | After contact with skin, wash immediately with plenty of ... (to be specified by the manufacturer). |
| S37/39 | Wear suitable gloves and eye/face protection.   |
| S61    | Avoid release to the environment. Refer to special instructions/safety data sheets.                 |

Contains epoxy-containing compounds. Observe manufacturer's instructions.

### Other regulations

as in Annex I of Directive 67/548/EEC

---

## 16. Other Information

Due to the merger of Degussa Construction chemicals and BASF Group all Material Safety Data Sheets have been reassessed on the basis of consolidated information. This may have resulted in changes of the Material Safety Data Sheets. In case you have questions concerning such changes please contact us under the address mentioned in Section I.

Full text of hazard symbols and R-phrases if mentioned as hazardous components in chapter 3:

|       |   |
|-------|---|
| Xi    | Irritant.   |
| N     | Dangerous for the environment.  |
| 36/38 | Irritating to eyes and skin.  |
| 43    | May cause sensitization by skin contact.  |
| 51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

---

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.