



The Chemical Company

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: **MASTERTOP® 1110 PEBBLE GREY PART A**

Company: BASF Construction Chemicals Singapore Pte Ltd

Address: 33 Tuas Avenue 11

Singapore 639090

Telephone number: +65 6861 6766

Facsimile: +65 6861 3186

Emergency telephone numbers: +65 6861 6766

2. HAZARDS IDENTIFICATION

Safety hazards: Not known.

Health hazards: Eye irritant. Skin irritant. May cause sensitisation in susceptible individuals by skin contact. Irritant if swallowed.

Environmental hazards: See section 12.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Mixture of modified epoxy resin with filler.

Hazardous Ingredients: Epoxy resin

CAS No: 25068-38-6

Hazard symbols: Xi

R-phrases: R36/R38-R43

% Concentration: <40%

4. FIRST AID MEASURES

Immediate treatment

Eye contact: While eyes are held open gently flush with water for 15 minutes.

Skin contact: Remove all contaminated clothing and shoes. Wash skin thoroughly with soap and water. Avoid solvents. Seek medical advice if irritation persists.

Inhalation: Remove to fresh air. Supply oxygen and / or artificial respiration as needed. Seek medical assistance as needed particularly in case of allergic response.

Ingestion: Do not induce vomiting. Contact doctor immediately. Rinse mouth and give glass of water.

Information for physicians: Treat symptomatically. Contact Poisons Information Center as needed. Allergic response as dermatitis or asthma-like symptoms / wheezing may occur after a single significant exposure and sensitization may occur after single or multiple minor exposures, depending on the individual.

MATERIAL SAFETY DATA SHEET

5. FIRE FIGHTING MEASURES

Special hazards: In case of fire oxides of carbon, nitrogen and other toxic gases are formed.
Protective equipment: Fire fighters should wear self-contained breathing apparatus in enclosed areas.
Extinguishing agents: Water spray, foam, carbon dioxide, dry powder.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear appropriate personal protection and ensure adequate ventilation.
Environmental precautions: Prevent discharge into drains, sewers and waterways.
Method for cleaning up: Absorb in inert dry material. Do not sweep up or wash down with water.

7. HANDLING AND STORAGE

Handling: Keep containers tightly closed when not in use.
Requirements for storage rooms: Keep dry and preferably keep cool.
Additional information: Keep separate from oxidizing materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Technical measures: Use mechanical mixing equipment and provide long handled brush for washing tools. Use only in well ventilated areas.

Personal protection

Respiratory protection: Use respiratory equipment in accordance to local safety requirements.
Eye protection: Wear safety glasses, which comply with local standards.
Hand protection: Wear gloves or suitable protective creams.
Body protection: Wear overalls or other suitable protective clothing.

MATERIAL SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Colour:	Pebble Grey
Odour:	Characteristic of epoxy resin
Freezing temperature:	n.d.
Boiling point:	>100°C
Melting point:	n.d.
Flash point:	n.as.
Vapour pressure:	n.d.
Vapour density:	n.d.
Relative density:	1.4 – 1.5
pH value:	11 approx.
Viscosity:	8000 - 12000 cps.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal storage and usage temperatures.
Hazardous reactions (conditions to avoid):	Avoid heat, and sources of ignition.
Materials to avoid:	Avoid oxidizing materials.
Hazardous decomposition products:	None under normal storage and use temperatures.

MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION

Acute toxicity (lethal dose)

LD50 oral Albino rat

Dose: n.d.
Additional information: n.d.
Information applies to: Mastertop 1110 Pebble Grey Part A

LC50 inhalation Albino rat

Dose: n.d.
Additional information: n.a.
Information applies to: Mastertop 1110 Pebble Grey Part A

Acute toxicity (irritation, sensitization etc.)

Eye irritation Albino rabbit

Result: n.d.
Symptoms: n.d.
Method: n.a.

Skin irritation Albino rabbit

Results: n.d.
Symptoms: n.d.
Method: n.a.

Delayed or chronic toxicological effects

Additional information: n.a.

MATERIAL SAFETY DATA SHEET

12. ECOLOGICAL INFORMATION

Ecotoxicity

LC50 dose: n.d.

Additional information

Ecotoxicity: Do not allow to be absorbed into soil. Prevent discharge into drains and waterways.

Biochemical oxygen demand

COD: n.d.

BOD: n.d.

Other: n.a.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local and governmental regulations.
Set resin and hardener can be disposed to landfill.

14. TRANSPORT INFORMATION

This product is not classified as a dangerous good under any transport regulations.

Road transport ADR / RID

Class: n.as.

Number/letter: n.as.

Warning sign: n.as.

Hazard No: n.as.

UN No: n.as.

Maritime / Air transport IMDG

UN No: n.as.

PG: n.as.

Class: n.as.

IMDG code page: n.as.

MATERIAL SAFETY DATA SHEET

15. REGULATORY INFORMATION

Classification: Required.
Hazard labels: Xi- Irritant.
R-phrases: R36/R38- Irritating to eyes and skin.
R43- May cause sensitization by skin contact.
S-phrases: S28- After contact with skin, wash immediately with plenty of water and soap.
S37/39- Wear suitable gloves and eye/face protection.

National regulatory information:

n.as.

Other regulations, restrictions and prohibitions:

n.a.

16. OTHER INFORMATION

Mastertop 1110 Pebble Grey Part A is part of a two-component epoxy resin system. Fully cured epoxy resin compositions, comprising mixed Part A and Part B, are considered non-toxic, non-irritant and non-sensitizing to the skin. Contact with the individual components during mixing and application should be minimised.

Reason for Issue: New format based on National Code of Practice for the preparation of MSDS – 2nd edition [NOHSC:2011(2003)]. Change of company name.

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request. All information contained in this MSDS is as accurate and up-to-date as possible. No warranty expressed or implied is made as to its accuracy, reliability or completeness.