

Safety data sheet

Page: 1/8

BASF Safety data sheet
Date / Revised: 17.11.2008
Product: **MASTERTOP 1200 HARDENER B4**

Version: 1.0

(30362451/SDS_GEN_SG/EN)

Date of print 13.03.2010

1. Substance/preparation and company identification

MASTERTOP 1200 HARDENER B4

Use: Product for construction chemicals

Company:

BASF South East Asia Pte Ltd.
7 Temasek Boulevard,
#35-01 Suntec Tower One, 038987, SINGAPORE
Telephone: +65 6 337-0330
Telefax number: +65 6 334-0330
E-mail address: tommy.chng@basf.com

Emergency information:

International emergency number:
Telephone: +49 180 2273-112

2. Composition/information on ingredients

Chemical nature

Blend based on: polyamine, modified

Hazardous ingredients

benzyl alcohol

Content (W/W): $\geq 25\%$ - $\leq 50\%$

CAS Number: 100-51-6

EC-Number: 202-859-9

INDEX-Number: 603-057-00-5

Hazard symbol(s): Xn

R-phrase(s): 20/22

1,5-Pentanediamine, 2-methyl-
Content (W/W): $\geq 5\%$ - $\leq 10\%$
CAS Number: 15520-10-2
Hazard symbol(s): T, C
R-phrase(s): 22, 23, 34

3-aminomethyl-3,5,5-trimethylcyclohexylamine
Content (W/W): $\geq 25\%$ - $\leq 50\%$
Hazard symbol(s): Xn
R-phrase(s): 21/22, 34, 43, 52/53

The wording of the hazard symbols and R-phrases is specified in chapter 16 if dangerous ingredients are mentioned.

3. Hazard identification

Corrosive.
Causes burns.
Also harmful by inhalation, in contact with skin and if swallowed.
May cause sensitization by skin contact.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. First-aid measures

General advice:
First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:
If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:
After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

On contact with eyes:
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

On ingestion:
Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Note to physician:
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary edema.

5. Fire-fighting measures

Suitable extinguishing media:
foam, water spray, dry extinguishing media, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Specific hazards:
carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, corrosive gases/vapours

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:
Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:
For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and storage

Handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:
The substance/product is non-combustible. The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

Protect from temperatures below: 5 °C
Protect from temperatures above: 35 °C

8. Exposure controls and personal protection

Components with workplace control parameters

benzyl alcohol, 100-51-6;

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic, alkaline compounds and toxic particles (e. g. EN 14387 Type ABEK-P3)

Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and other
Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

acid- resp. lye-proof apron, e.g. of rubber (f.e. according to EN 14605), Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and chemical properties

Form: liquid
Colour: yellowish
Odour: characteristic

BASF Safety data sheet
Date / Revised: 17.11.2008
Product: **MASTERTOP 1200 HARDENER B4**

Version: 1.0

(30362451/SDS_GEN_SG/EN)

Date of print 13.03.2010

boiling temperature: > 100 °C
Viscosity, dynamic: 300 mPa.s
(approx. 25 °C)

10. Stability and reactivity

Conditions to avoid:
See MSDS section 7 - Handling and storage.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
zinc, aluminium, oxidizing agents, strong alkalies, acids, mild steel, carbon steel (iron)

Corrosion to metals: No data available.

Hazardous reactions:
The product is stable if stored and handled as prescribed/indicated.

11. Toxicological information

Acute toxicity

Information on: 3-aminomethyl-3,5,5-trimethylcyclohexylamine
LD50 rat (oral): 1,030 mg/kg
Literature data.

Information on: 3-aminomethyl-3,5,5-trimethylcyclohexylamine
(by inhalation): No data available.

Sensitization

Information on: 3-aminomethyl-3,5,5-trimethylcyclohexylamine
Guinea pig maximization test guinea pig: sensitizing (OECD Guideline 406)
Literature data.

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological information

Ecotoxicity

Information on: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Information on: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Aquatic invertebrates:

EC50 (48 h) 23 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The details of the toxic effect relate to the nominal concentration.

Additional information

Other ecotoxicological advice:

There is a high probability that the product is not acutely harmful to aquatic organisms. Do not release untreated into natural waters. The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal considerations

Observe national and local legal requirements.

Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport information

Domestic transport:

Hazard class:	8
Packing group:	III
ID number:	UN 2735
Hazard label:	8
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (contains ISOPHORONEDIAMINE)

Sea transport

IMDG

Hazard class:	8
Packing group:	III
ID number:	UN 2735
Hazard label:	8
Marine pollutant:	YES
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (contains ISOPHORONEDIAMINE)

Air transport

IATA/ICAO

BASF Safety data sheet
 Date / Revised: 17.11.2008
 Product: **MASTERTOP 1200 HARDENER B4**

Version: 1.0

(30362451/SDS_GEN_SG/EN)

Date of print 13.03.2010

Hazard class:	8
Packing group:	III
ID number:	UN 2735
Hazard label:	8
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (contains ISOPHORONEDIAMINE)

15. Regulatory information

Regulations of the European union (Labelling)

EEC Directives:

Hazard symbol(s) C	Corrosive.
R-phrase(s) R34 R20/21/22 R43 R52/53	Causes burns. Harmful by inhalation, in contact with skin and if swallowed. May cause sensitization by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrase(s) S36/37/39 S27/28	Wear suitable protective clothing, gloves and eye/face protection. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of ... (to be specified by the manufacturer).
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

Hazard determining component(s) for labelling: ISOPHORONEDIAMINE

Other regulations

16. Other information

Due to the merger of Degussa Construction chemicals and BASF Group all Material Safety Data Sheets have been reassessed on the basis of consolidated information. This may have resulted in changes of the Material Safety Data Sheets. In case you have questions concerning such changes please contact us under the address mentioned in Section I.

Full text of hazard symbols and R-phrases if mentioned as hazardous components in chapter 2:

Xn	Harmful.
T	Toxic.

BASF Safety data sheet

Date / Revised: 17.11.2008

Product: **MASTERTOP 1200 HARDENER B4**

Version: 1.0

(30362451/SDS_GEN_SG/EN)

Date of print 13.03.2010

C	Corrosive.
20/22	Harmful by inhalation and if swallowed.
22	Harmful if swallowed.
23	Toxic by inhalation.
34	Causes burns.
21/22	Harmful in contact with skin and if swallowed.
43	May cause sensitization by skin contact.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.