

Safety data sheet

Page: 1/6

BASF Safety data sheet
Date / Revised: 30.11.2009
Product: **UCRETE LIQUID PIGMENT GREY**

Version: 2.0

(30445488/SDS_GEN_SG/EN)

Date of print 03.11.2010

1. Substance/preparation and company identification

UCRETE LIQUID PIGMENT GREY

Use: Product for construction chemicals

Company:

BASF South East Asia Pte Ltd.
7 Temasek Boulevard,
#35-01 Suntec Tower One, 038987, SINGAPORE
Telephone: +65 6 337-0330
Telefax number: +65 6 334-0330
E-mail address: tommy.chng@basf.com

Emergency information:

International emergency number:
Telephone: +49 180 2273-112

2. Composition/information on ingredients

Chemical nature

Preparation based on: dispersion, polyol, modified

3. Hazard identification

This product is not expected to pose a health risk if handled in accordance with the health and safety advice provided in this safety data sheet.

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

After contact with skin, wash immediately with plenty of water and soap. If irritation develops, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Note to physician:

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Suitable extinguishing media:

foam, water spray, dry extinguishing media, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

BASF Safety data sheet
Date / Revised: 30.11.2009
Product: UCRETE LIQUID PIGMENT GREY

Version: 2.0

(30445488/SDS_GEN_SG/EN)

Date of print 03.11.2010

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

No special precautions necessary.

Storage

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Store protected against freezing. Protect from direct sunlight.

Protect from temperatures below: 5 °C

The packed product must be protected from temperatures below the indicated one.

8. Exposure controls and personal protection

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type ABEK).

Hand protection:

impermeable gloves

Synthetic rubber gloves

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

light protective clothing

General safety and hygiene measures:

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do

BASF Safety data sheet
Date / Revised: 30.11.2009
Product: UCRETE LIQUID PIGMENT GREY

Version: 2.0

(30445488/SDS_GEN_SG/EN)

Date of print 03.11.2010

not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Colour:	grey	
Odour:	product specific	
Flash point:	> 100 °C	(DIN 53213-1)
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Density:	approx. 1.00 g/cm ³ (20 °C)	
Solubility in water:	not soluble	

10. Stability and Reactivity

Conditions to avoid:

See MSDS section 7 - Handling and storage.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

11. Toxicological Information

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Additional information

Other ecotoxicological advice:

Do not allow to enter soil, waterways or waste water channels. The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal Considerations

Observe national and local legal requirements.
Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:
Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Regulations of the European union (Labelling)

Directive 1999/45/EC ('Preparation Directive'):

The product does not require a hazard warning label in accordance with EC Directives.

Other regulations

16. Other Information

Due to the merger of Degussa Construction chemicals and BASF Group all Material Safety Data Sheets have been reassessed on the basis of consolidated information. This may have resulted in changes of the Material Safety Data Sheets. In case you have questions concerning such changes please contact us under the address mentioned in Section I.

BASF Safety data sheet

Date / Revised: 30.11.2009

Product: **UCRETE LIQUID PIGMENT GREY**

Version: 2.0

(30445488/SDS_GEN_SG/EN)

Date of print 03.11.2010

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.